



CLASS 1

Building Product Information Sheet

Product name:

Untreated Non-Structural Appearance Grade V-Groove Plywood

Product line (the product line from which the product is customised):

Black Forest V-Groove Ply

Product description and its intended use (measurements, materials, usage):

Untreated Non-Structural V-Groove Plywood 2400x1200x9mm

Available Sizes: 9mm or 12mm x 1200x2400mm

Product Identifiers in order above: BFUTAB9VNS and BFUTAB12VNS

Black Forest Non-Structural Untreated Ply is specifically produced for non-structural, non-load-bearing applications or applications where compliance with NZ Building Code is not required. Black Forest V-Groove Ply is an appearance grade ply intended for any application that requires a visual quality finish such as, wall or ceiling linings, furniture, joinery and cabinetry, caravans, shop or vehicle fitouts, decorative panels, desks or countertops, and many other DIY uses. V-Groove Ply has a visual negative detail running across the sheets at 100mm centres. Non-structural plywood must not be used for any application requiring a building consent or where structural performance is required. Non-structural plywood must not be used in any structural or load bearing application as outlined under the NZ Building Code. Non-structural plywood is not compliant with AS/NZS 2269.

Species Radiata with a Poplar Core
Grade A/D Face Quality
Treatment Untreated

Features
V-groove at 100mm Centres

Place of manufacture: China

Legal and trading name of the manufacturer(s):

Xuzhou Jafrey International Co., Ltd

Legal and trading name of the importer (if applicable):

Black Forest Investments NZ Limited

Address for service:

BDO Christchurch, Awly Building, Level 4, 287-293 Durham Street
Christchurch, New Zealand 8140

Website:

blackforestnz.com

Email:

admin@blackforestnz.com

Phone:

021-194-7088

NZBN:

9429042285861



Te Kāwanatanga o Aotearoa
New Zealand Government

Relevant Building Code clauses:

N/A

Statement on how the building product is expected to contribute to compliance:

N/A

Limitations on the use of the building product:

Not suitable for structural applications. Appearance grade plywood is not suitable for exterior applications or situations where it may come into contact with moisture and dampness.

Design requirements that would support the use of the building product:

When used in construction, particularly work deemed to be Restricted Building Work (RBW) as defined in the Building (Definition of Restricted Building Work) Order 2011 it's use should be in accordance with the specifications set out in NZS3604.2011 Timber framed buildings or NZS/AS1720 Part 1.2022 Timber structures. Before undertaking any construction work you must consult with your local authority to check than any construction requirements are met and to determine if a Building Consent is required. A qualified tradesman should be consulted where expert services may be required.

Installation requirements:

When used in Restricted Building Work as defined in the Building (Definition of Restricted Building Work) Order 2011 plywood must be installed by a Licensed Building Practitioner with appropriate certification. No special precautions are required for plywood products in purchased form. Local ventilation should be provided to assure formaldehyde exposure limits are met. Under foreseeable conditions of use, avoid repeated breathing of wood dust. Local ventilation should be provided to remove wood dust from workspaces and to keep within formaldehyde exposure limits. Users should wear protective gloves and goggles. When handling or working on panel products to prevent injury.

Maintenance requirements:

Keep dry and protected at all times. Wipes surfaces clean with non-abrasive cleaning products such as a mild detergent and damp cloth with care to keep the surfaces as dry as possible.

Is the building product/building product line subject to warning or ban under section 26?:

No

If yes, description of the warning or ban under section 26:

N/A

Date: 10/11/2023