



CLASS 1

Building Product Information Sheet

Product name:

Standard Formply

Product line (the product line from which the product is customised):

Black Forest Formply

Product description and its intended use (measurements, materials, usage):

Formply 2440x1220x17mm Poplar Core Standard Grade Film Face

Available Sizes: 17mm x 1220x2440mm

Product Identifiers in order above: BFSFORM17

Black Forest Standard Formply is a non-structural plywood with a Poplar core designed for use in the concrete forming industry where structural or load bearing applications are not required. Suitable for formwork where bracing elements are not required. Film coated on 2 sides for easy installation. Not to be used in a structural application. If maintained correctly it can be reused. The glue used to make Formply, along with the laminated exterior, provides the product with resilience to the elements.

Species Poplar Core

Grade Standard Grade Film Face.

Treatment N/A

Features

A S 6669 Certified

Place of manufacture: China

Legal and trading name of the manufacturer(s):

Shandong Rogge Wood Industry Co. Ltd. Trading as Ayaya International Trading Limited, Xuzhou Jafray International Co., Ltd

Legal and trading name of the importer (if applicable):

Black Forest Investments NZ Limited

Address for service:

BDO Christchurch, Awly Building, Level 4, 287-293 Durham Street
Christchurch, New Zealand 8140

Website:

blackforestnz.com

Email:

admin@blackforestnz.com

Phone:

021-194-7088

NZBN:

9429042285861



Te Kāwanatanga o Aotearoa
New Zealand Government

Relevant Building Code clauses:

Manufactured in accordance with the Australian Standard AS 6669:2016 Plywood — Formwork; Specifies requirements for the manufacture, grading, finishing and branding of plywood used specifically in formwork

Statement on how the building product is expected to contribute to compliance:**Limitations on the use of the building product:**

Not suitable for structural applications.

Design requirements that would support the use of the building product:

When used in construction, particularly work deemed to be Restricted Building Work (RBW) as defined in the Building (Definition of Restricted Building Work) Order 2011 it's use should be in accordance with the specifications set out in NZS3604.2011 Timber framed buildings or NZS/AS1720 Part 1.2022 Timber structures. Before undertaking any construction work you must consult with your local authority to check than any construction requirements are met and to determine if a Building Consent is required. A qualified tradesman should be consulted where expert services may be required.

Installation requirements:

When used in Restricted Building Work as defined in the Building (Definition of Restricted Building Work) Order 2011 FormPly must be installed by a Licensed Building Practitioner with appropriate certification in accordance with NZ3604:2011 specifications. No special precautions are required for plywood products in purchased form. Local ventilation should be provided to assure formaldehyde exposure limits are met. Under foreseeable conditions of use, avoid repeated breathing of wood dust. Local ventilation should be provided to remove wood dust from workspaces and to keep within formaldehyde exposure limits. Users should wear protective gloves and goggles. When handling or working on panel products to prevent injury.

Maintenance requirements:

Ensure that FormPly is shielded from prolonged exposure to moisture and is not subjected to elevated moisture levels, especially in applications that are concealed from view or lack easy access for inspection.

Is the building product/building product line subject to warning or ban under section 26?:

No

If yes, description of the warning or ban under section 26:

N/A

Date: 10/11/2023